

BRANIFF

WATER SOLUTIONS

Model

▪ BRESCIA EL TOP SPUD BOWL

▪ 72.7302.23.B


FLUX TOILET

| Features

- **Toilet Style:** Flux Toilet
- **Color:** White
- **Material:** Vitreous China
- **Flushing System:** Fluxometer
- **Operation:** Siphon Jet
- **High-Efficiency Toilet:** 1.28 gpf / 4.8 lpf
- **Average Weight:** 48.23 lbs
- **Average Height:** 15 "
- **Water Surface:** 11 " x 13 ¾ "
- **Flushes:** 600 grams of solids
(Internal Braniff Lab)
- **Trapway Diameter:** 2" Fully Glazed Trapway
- **Working Pressure:** Minimum and maximum pressure of 80 lbs/in²



| Components



#	Description	Code	QTY
1	Brescia EL top spud bowl	B2H02A	1
2	Bolt caps	280122822	1
3	Installation kit	223122861	1
4	Spud	470733ARM	1

* Seat Not Included

| Specifications

- ASME A112.19.2-2018/CSA B45.1-18
- EPA WaterSense High Efficiency Toilets




10 Years Warranty on Vitreous China |

| Tecnical Data

Section	Measures
A	28 ½ "
B	14 ½ "
C	5 ½ "
D	3 ⅜ "
E	15 "
F	12 "
G	10 "
H	20 ¼ "
I	6 "
J	4 ½ "

* Dimension tolerance of $\pm 5\%$



| Instalation

Clean the installation area and make sure the distances are correct. Turn bowl upside down on cloth and place wax ring, carefully align and lower bowl over floor flange and floor mounting bolts. Assemble snap-on base and place the metallic washers and tighten nuts.

| Recomendations

- Before connecting to the hydraulic network, verify that the distance between the wall and the toilet discharge coincide with the entrance of the hydraulic network.
- The toilet is fragile and may break during manipulation, use gloves are recommended during installation.
- Don't use chlorine cleaning tablets in the tank, this can damage the valves.
- Use antifungal silicone sealant for the joints of the toilet with the floor, don't use cement or adhesive plaster.
- When installing the fixing screws, take care not to exceed the tightening force of the nuts, as this can break the toilet.
- Hand tighten the supply hose (not included) to the tank, if there is any leak, lightly tighten with a tool, do not use any type of sealant in the joints.

| Maintenance

- Clean the surface with a water-damped cloth.
- Never use cutting items, fibers, sandpapers, detergents, solvents, liquids or abrasive powders to clean the bowl.

| Warranty

All products commercialized by BRANIFF are designed, manufactured and tested accordingly to our quality system and to international standards if any manufacturing or workmanship defect were to be presented on the product and corroborated by BRANIFF, it will be replace it without cost to buyer. Finishes are warranted against manufacturing defects for 10 (ten) years on vitreous china and 1 (one) year on moving parts and accesories.

10 Years Warranty on Vitreous China |